



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>H01L 21/68</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/66549</b> <b>(43) International Publication Date:</b> 23 December 1999 (23.12.99)
<b>(21) International Application Number:</b> PCT/GB99/01896 <b>(22) International Filing Date:</b> 15 June 1999 (15.06.99)  <b>(30) Priority Data:</b> 9812850.7                      16 June 1998 (16.06.98)                      GB  <b>(71) Applicant (for all designated States except US):</b> SURFACE TECHNOLOGY SYSTEMS LIMITED [GB/GB]; Imperial Park, Newport, Gwent NP1 9UJ (GB).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> THOMAS, Tudor, Norman [GB/GB]; 4 Severn Grove, Pontcanna, Cardiff CF1 9EN (GB). WILLIAMS, Robert, John [GB/GB]; 72 Pengam Street, Glan y Nant, Blackwood, Gwent NP2 1XJ (GB).  <b>(74) Agents:</b> JAMES, Michael, John, Gwynne et al.; Wynne-Jones, Laine & James, Essex Place, 22 Rodney Road, Cheltenham GL50 1JJ (GB).		<b>(81) Designated States:</b> JP, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> METHOD AND APPARATUS FOR DECHUCKING A SUBSTRATE FROM AN ELECTROSTATIC CHUCK  <div data-bbox="428 1192 1068 1390" data-label="Image"> </div> <b>(57) Abstract</b> <p>There is provided a method of dechucking from an electrostatic chuck a substrate held by one or more residual forces to the chuck, the method comprising the steps of: (a) reducing a residual chucking force due to the electrostatic chuck polarisation; (b) contracting the chuck with the substrate attached thereto with a plasma for a time sufficient substantially to remove any residual charge from the surface of the substrate and the chuck; and (c) subsequently to, or simultaneously with, step (b) removing the substrate from the chuck. Also disclosed is an apparatus for performing the method.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## METHOD AND APPARATUS FOR DECHUCKING A SUBSTRATE FROM AN ELECTROSTATIC CHUCK

This invention relates to a method and apparatus for dechucking a substrate particularly, although not exclusively, a semi-conductor wafer from an electrostatic  
5 chuck.

Electrostatic chucks have been used to hold semiconductor wafers and other materials whilst processing in a vacuum chamber. Electrostatic chucks have been used in some cases in preference to mechanical clamping devices to avoid the  
10 need for fingers or the like which may damage the surface of the wafer. However, with the use of electrostatic chucks, it has been found that residual forces holding the wafer to the chuck exist even after the clamping voltage is removed after processing.

15 US 5684669 and US 5325261 disclose methods aimed at minimising the residual electrostatic force between the wafer and chuck by applying a voltage, which is typically of the same polarity as (but smaller than) the chucking voltage, during release of the wafer. US 5684669 uses the  
20 leak rate of gas which seeps through the gap between the wafer and the chuck to measure the residual force indirectly. US 5325261 monitors the extent of the residual force indirectly by measuring the chuck capacitance.

25 US 5221450 discloses an electrostatic chucking method in which a chuck is immersed in a plasma without the wafer on it in order to remove the remaining charges before the next wafer is held.

It has been found that there are two main sources of stiction in an electrostatic chuck. The first of these discussed above is the residual electrostatic polarisation, of the dielectric material of the electrostatic chuck itself which causes bound surface charge to bind the wafer by electrostatic attraction. The second source relates to residual free charges which are due to either leakage current through or from the surface of the chuck dielectric or derived from the process itself, which reside on the chuck or the wafer surface. Whilst the first problem is addressed by the methods described in US 5325261 and US 5684669, it has been found that these methods do not work in an entirely satisfactory manner as they do not address the issue of the second source of stiction before or during wafer removal.

According to a first aspect of the present invention, there is provided a method of dechucking from an electrostatic chuck a substrate held by one or more residual forces to the chuck, the method comprising the steps of:

- (a) reducing a residual chucking force due to the electrostatic chuck polarisation;
- (b) contacting the chuck with the substrate attached thereto with a plasma for a time sufficient substantially to remove any residual charge from the surface of the substrate and the chuck; and
- (c) subsequently to, or simultaneously with, step (b) removing the substrate from the chuck.

Preferably, the chuck with the substrate attached

thereto is substantially immersed in the plasma.

The contact with or immersion in the plasma may be  
carried out in any suitable manner, specific examples being  
immersion in a driven plasma and immersion in, for example,  
5 a downstream plasma. Discharging works, for example, both  
with a coil discharge and a coil and a platen discharge.

The residual chucking force may be the residual  
electrostatic polarisation referred to above.

The residual chucking force may be minimised by any  
10 method known in the art, in particular the methods disclosed  
in US 5325261 and US 5684669, and it is therefore not  
proposed to discuss these in further great detail here.  
However, it is preferred that the chucking force is  
minimised by applying a first voltage to the chuck. In a  
15 particular embodiment, the preferred magnitude of the first  
voltage is determined by ramping the voltage down whilst  
measuring the extent to which the substrate is held to the  
chuck. Preferably, when a minimum in the residual chucking  
force is found, the preferred magnitude of the first voltage  
20 is held for a desired period. The extent to which the  
substrate is held may be measured by, for example, the  
methods disclosed in US 5325261 or US 5684669. For example,  
US 5325261 monitors the extent of the residual force by  
measuring the chuck capacitance, as mentioned above. The  
25 value of the capacitance depends on how closely the  
substrate is held to the chuck. As substrates, particularly  
in the form of wafers, may have some degree of bowing, the  
force holding the substrate to the chuck may be counteracted

by internal stress in the substrate. As the residual clamping force decreases, the substrate's natural bow is restored and as this happens the substrate capacitance may decrease. Alternatively, as described in US 5684669, the  
5 residual force may be monitored by measuring the leak rate of a gas which seeps through the gap between the substrate and the chuck.

The chuck may be of any appropriate form. Thus, it may be flat as disclosed in US 5325261. Alternatively, it may  
10 have one or more steps on its upper surface adjacent the substrate, as also disclosed in US-A-5325261, for example around the periphery of the upper surface.

It is to be noted that, in the method of the present invention, the substrate is still present on the chuck on  
15 immersion in a plasma. It may also be subsequently lifted whilst being immersed in a plasma.

Any suitable plasma can be used for the contact or immersion. For example, argon or another inert gas may be present to prevent further etching of the substrate. SF<sub>6</sub>  
20 and/or other electronegative gases (eg. oxygen) may be present in the plasma and may improve charge removal. Any suitable power which sustains a plasma may be used, but typical examples are within the range 50W to 800W.

The time sufficient to remove the residual charge may  
25 be determined by monitoring the capacitance of the chuck due to the proximity of the substrate. Any time may be applicable, but it is typically in the range of between about one second and one minute. It has been found that, in one

embodiment, the time sufficient substantially to remove the residual charge is typically about one second.

Preferably, a second voltage is applied to the chuck during contact of the chuck and substrate with the plasma.

5 Whilst any suitable voltage may be used (including a zero voltage) for the second voltage, in a preferred embodiment it is the same as the first voltage.

✓ The applicant has found that reversing steps (a) and (b) of the method of the invention does not lead to efficient removal of the residual charges.  
10

According to a second aspect of the present invention, there is provided an apparatus for performing the method described above comprising:

(a) a chamber within which a substrate held on an electrostatic chuck may be processed;  
15

(b) means for reducing a residual force due to the electrostatic chuck; and

(c) means for providing a plasma to contact the chuck with the substrate attached thereto or being removed therefrom  
20 for a time substantially to remove any residual charge from the surface of the substrate and the chuck.

The apparatus may further comprise means for removing the substrate from the chuck. In a preferred embodiment, means may be provided to apply a voltage to the chuck.

25 Although the invention has been defined above, it is to be understood that it includes any inventive combination of the features set out above or in the following description.

The invention may be performed in various ways and a

specific example will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is an enlarged cross sectional view of one embodiment of the electrostatic chuck and wafer; and

5        Figure 2 is a schematic view of one embodiment of an apparatus used in accordance with the invention.

Referring to Figure 1, there is shown an electrostatic chuck generally at 1. The chuck 1 comprises a dielectric insulator portion 2 having a reference electrode 3 mounted  
10 on its lower surface. The dielectric portion 2 has, within its body, electrodes 4 and 5. Although it is not shown in the drawings, a step may be formed around the periphery of the upper surface of the chuck (this aids dechucking by deliberate bow of a wafer positioned on the chuck).  
15 Positioned over the electrostatic chuck 1 is a semi conductor wafer 6.

In use, when a voltage is applied to the electrodes 4 and 5, the wafer 6 is held against the upper surface of the chuck 1. Chuck 1 is placed upon the electrode 3 which can  
20 either be driven (rf or dc power) or grounded or allowed to electrically float. Indeed chuck 1 can replace the electrode 3 completely in some applications. The applied power to the electrode surface serves (in a triode configuration) to independently (from the plasma excitation power input)  
25 bias the electrode to a potential with respect to the grounded surfaces. This potential is typically used to drive ions towards the workpiece.

When the wafer 6 is held to the electrostatic chuck 1



in the manner described above, processing of the wafer, for example by etching or deposition, may be carried out by methods known in the art.

Figure 2 shows one embodiment of an apparatus in accordance with the invention. A vacuum chamber is shown generally at 7 having the support electrode 3 on which is positioned the electrostatic chuck 1. Also within the chamber is a spaced electrode 8. The wafer 6 is held against the chuck 1 by electrostatic forces as described above. It may be cooled by backside cooling means (not shown). The chamber 7 is surrounded by a coil 9 and fed by an RF source 10 which is used to induce a plasma in the chamber 7 between electrodes 3 and 8 during processing. When immersion in a plasma occurs the inductive discharge in the specific example is typically about 13cm above the wafer with RF power applied to the chuck 1 and wafer 6, although any value could be used for example from a few cm to greater than 20cm. The chamber is provided with a gas inlet port 11 through which deposition or etched gases, for example, can be introduced and an exhaust port 12 for the removal of gaseous process products and any excess process gas. The operation of such a reactor in terms of the processing (eg. etch/deposition) of the wafer 6 is well known in the art.

Once processing of the wafer 6 has been carried out and it is required to dechuck (remove) the wafer 6 from the chuck 1, a value of voltage is determined which may be applied to the electrodes 4 and 5. The magnitude of this voltage can be found by any appropriate means, but one

example is by ramping the clamping voltage down whilst measuring the extent to which a wafer is clamped, that is by indirect measurement of the residual clamping force. One example of how this may be carried out has been used in US 5325261. When a minimum in the clamping force is indicated the voltage is held at this level. However, as indicated above, the present invention further reduces the stiction in any electrostatic chuck by reducing the residual free charges, due to either leakage current through the chuck dielectric 2 or derived from the process itself, which reside on the chuck and/or wafer surface. Thus, as a subsequent step, the wafer 6 on the electrostatic chuck 1 is "immersed" in a plasma within chamber 7 for a time sufficient to remove the residual charge from the surface of the wafer and the surface of the electrostatic chuck which period is about 1 second in one embodiment. The immersion may be in a driven plasma or, for example, a downstream plasma. A voltage which is found to cancel the residual polarisation as described in US 5325261 may be applied to electrodes 4 and 5 in chuck 1 whilst the wafer is immersed in the discharge plasma. However, the voltage can be set to zero during the discharge and then reapplied for removal of wafer 6. Alternatively, the wafer may be removed during the plasma discharge.

When immersion in a downstream plasma occurs the inductive discharge in the example is typically about 13cm above the wafer with no RF power applied to the wafer. Alternatively, the inductive discharge may typically be

about 13cm above the wafer with RF power applied to the chuck 1 and wafer 6. In both cases, again, any value could be used, for example from a few cm to greater than 20cm.

CLAIMS

1. A method of dechucking from an electrostatic chuck a substrate held by one or more residual forces to the chuck, the method comprising the steps of:

5 (a) reducing a residual chucking force due to the electrostatic chuck polarisation;

(b) contacting the chuck with the substrate attached thereto with a plasma for a time sufficient substantially to remove any residual charge from the surface of the substrate  
10 and the chuck; and

(c) subsequently to, or simultaneously with, step (b) removing the substrate from the chuck.

2. A method according to Claim 1, wherein the chuck with the substrate attached thereto is substantially immersed in  
15 the plasma.

3. A method according to Claim 1 or 2, wherein the chuck is contacted with the plasma by immersion in a driven plasma or immersion in a downstream plasma.

4. A method according to any preceding claim, wherein the  
20 chucking force is reduced by applying a first voltage to the chuck.

5. A method according to Claim 4, wherein the preferred magnitude of the first voltage is determined by ramping the voltage down whilst measuring the extent to which the  
25 substrate is held to the chuck.

6. A method according to Claim 5, wherein, when a minimum in the residual chucking force is found, the preferred magnitude of the first voltage is held for a desired period.

7. A method according to Claim 5 or 6, wherein the extent to which the substrate is held to the chuck is monitored by measuring the chuck capacitance.

8. A method according to Claim 5 or 6, wherein the extent  
5 to which the substrate is held to the chuck is monitored by measuring the leak rate of a gas which seeps through the gap between the substrate and the chuck.

9. A method according to any preceding claim, wherein the plasma comprises argon, another inert gas, SF<sub>6</sub> and/or an  
10 electronegative gas.

10. A method according to any preceding Claim, wherein a time sufficient to remove the residual force is determined by monitoring the capacitance of the chuck due to the proximity of the substrate.

15 11. A method according to any one of Claims 4 to 10, wherein a second voltage is applied to the chuck during contact of the chuck and substrate with the plasma.

12. A method according to Claim 11, wherein the second voltage is the same as the first voltage.

20 13. An apparatus for performing the method according to any preceding Claim, the apparatus comprising:

(a) a chamber within which a substrate held on an electrostatic chuck may be processed;

(b) means for reducing a residual force due to the  
25 electrostatic chuck; and



(c) means for providing a plasma to contact the chuck with the substrate attached thereto or being removed therefrom for a time substantially to remove any residual

charge from the surface of the substrate and the chuck.

14. An apparatus according to Claim 13, further comprising means for removing the substrate from the chuck.

15. An apparatus according to Claim 13 or 14, further  
5 comprising means to apply a voltage to the chuck.

1/1

**Fig. 1****Fig. 2**

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/01896

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H01L21/68

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 709 877 A (HITACHI LTD) 1 May 1996 (1996-05-01)	1,2,9,13
A	column 3, line 13 - column 4, line 19; figures 1,2	3
A	EP 0 680 083 A (APPLIED MATERIALS INC) 2 November 1995 (1995-11-02) the whole document	1,4,5,8, 13-15
A	EP 0 798 775 A (NIPPON ELECTRIC CO) 1 October 1997 (1997-10-01) the whole document	1-15
A	WO '98 00861 A (BENJAMIN NEIL MARTIN PAUL ;KUBLY MARC B (US); LAM RES CORP (US); G) 8 January 1998 (1998-01-08) the whole document	1-15
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

27 August 1999

Date of mailing of the international search report

02/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kirkwood, J



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/01896

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 095, no. 004, 31 May 1995 (1995-05-31) & JP 07 022498 A (OKI ELECTRIC IND CO LTD), 24 January 1995 (1995-01-24) abstract	1-15
A	PATENT ABSTRACTS OF JAPAN vol. 018, no. 336 (E-1568), 24 June 1994 (1994-06-24) & JP 06 085045 A (FUJITSU LTD;OTHERS: 01), 25 March 1994 (1994-03-25) abstract	1-15
A	US 5 699 223 A (SAKAMOTO KIYOTAKA ET AL) 16 December 1997 (1997-12-16) the whole document	1-15
P,A	US 5 818 682 A (LOO DAVID H) 6 October 1998 (1998-10-06) the whole document	1-15
A	US 5 325 261 A (HORWITZ CHRISTOPHER M) 28 June 1994 (1994-06-28) cited in the application the whole document	1,4-7, 10,13-15
A	US 5 684 669 A (COLLINS KENNETH S ET AL) 4 November 1997 (1997-11-04) cited in the application the whole document	1-15
A	US 5 221 450 A (HATTORI KEI ET AL) 22 June 1993 (1993-06-22) cited in the application the whole document	1-15
A	US 5 612 850 A (PYATIGORSKY GRIGORY ET AL) 18 March 1997 (1997-03-18) the whole document	1-15

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/01896

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0709877 A	01-05-1996	JP 8279487 A	22-10-1996
		JP 8279486 A	22-10-1996
		US 5681424 A	28-10-1997
		EP 0938134 A	25-08-1999
		WO 9428578 A	08-12-1994
EP 0680083 A	02-11-1995	US 5491603 A	13-02-1996
		JP 8064664 A	08-03-1996
EP 0798775 A	01-10-1997	JP 9260475 A	03-10-1997
WO 9800861 A	08-01-1998	US 5793192 A	11-08-1998
		AU 3585197 A	21-01-1998
		EP 0907964 A	14-04-1999
JP 07022498 A	24-01-1995	NONE	
JP 06085045 A	25-03-1994	NONE	
US 5699223 A	16-12-1997	JP 8017808 A	19-01-1996
US 5818682 A	06-10-1998	NONE	
US 5325261 A	28-06-1994	DE 4216218 A	19-11-1992
		FR 2676603 A	20-11-1992
		JP 7029968 A	31-01-1995
US 5684669 A	04-11-1997	US 5874361 A	23-02-1999
US 5221450 A	22-06-1993	JP 4099024 A	31-03-1992
		JP 6103683 B	14-12-1994
		KR 9506346 B	14-06-1995
US 5612850 A	18-03-1997	US 5459632 A	17-10-1995
		DE 69510419 D	29-07-1999
		EP 0700593 A	13-03-1996
		JP 9502078 T	25-02-1997
		WO 9524764 A	14-09-1995